



-Not to scale-

Cable Construction				
- Number of fibers	4	6	8	12
- Number of loose tubes	1 central tube			
- Loose tube	PBT			
-Material	3,0 ± 3% mm			
-Diameter	Thixotropic jelly			
-Type of filling compound	Glass yarn with water blocking elements			
- Peripheral strength member	Corrugated steel tape			
- Material	MDPE			
- Armor & rodent protection	1,5 mm (nominal)			
-Material	8,8 mm ± 0,2			
- Outer Sheath	78 kg/km			
- Material				
- Thickness				
- Cable diameter				
- Cable weight (approx.)				

- Mechanical characteristics		(All optical measurements at 1550 nm)	
Test	Test Standard	Specified Value	Acceptance Criteria
- Tensile Force Installation Operation	IEC 60794-1-2-E1	Max. 800 N Max. 200 N	$\Delta\alpha$ reversible, fiber strain 0.33 % $\Delta\alpha = <0,05$ dB
- Cable Bend With load Without load	IEC 60794-1-2-E11	R= 20 x D, 4 turns, 3 cycles R= 15 x D, 4 turns, 3 cycles	$\Delta\alpha = <0,05$ dB, no damage
- Impact	IEC 60794-1-2-E4	5 Nm, 3 impacts at different points, R= 10 mm,	No damage on tubes
- Repeated bending	IEC 60794-1-2-E6	R= 20 x D, 10 N load, 30 cycles, t ≤ 2 min/10 cycles	No damage
- Crush Resistance	IEC 60794-1-2-E3	Max. 2000 N/100 mm.	$\Delta\alpha = <0,05$ dB, no damage

- Environmental Characteristics			
Test	Test Standard	Specified Value	Acceptance Criteria
- Water penetration	IEC 60794-1-2-F5B	3 meter specimen, 1 m water altitude	No leaked from the opposite end of the cable in 24 hours.
- Temperature cycling	IEC 60794-1-2-F1	-30 to + 70 °C	$\Delta\alpha = <0,05 \text{ dB/km}$ at 1550 nm

- Identification	
- Cable Marking	1m \pm 1% Intervals in white color with hot print.
- Identification of cable ¹	CENKABLO <year of manufacture> <number of fibers> FO <type of fibers> <length marking in meter>
- Color of loose tube ²	Natural
- Color of fibers ²	1.Red, 2.Green, 3.Blue, 4.Yellow, 5.White, 6.Grey, 7.Brown, 8.Violet, 9.Turquoise, 10.Black, 11.Orange, 12.Pink
- Color of outer sheath ²	Black

¹ This inscription is standard imprint. It can be changed according to request.

² The other tube, fiber and sheath colors are optional.

- Delivery Information	
- Drum length/Tolerance ³	2000 m \pm 5%
- Drum Flange diameter ³	900 mm
- Drum core diameter ³	500 mm
- Outside width ³	780 mm
- Central hole diameter	85 mm

³ Drum dimensions can change depends on cable length on a drum. Standard delivery length is 2 km. Other delivery lengths are optional.

- Transmission characteristics
-Refer to fiber data